



Surface Magnetic Contact

Code: SC513/WH/4C

SC513 | Surface Contact | Grade 2 | White | Non-resistored

This compact surface mounted magnetic contact can be used in security systems up to and including security grade 2 & environmental class II (for use indoors) as specified in EN50131-1 and is compliant to EN50131-2-6. It operates as a normally closed circuit going open when the magnet housing is moved away from the contact housing. This contact can be used on window and doors to detect the unauthorised entry of an intruder, it is pre-wired and potted for added protection

Features & Benefits

- Surface mounted contact.
- Sealed for increased moisture resistance.
- Pre-wired
- EN50131-2-6 Grade 2
- Environmental Class II



Security

EN50131-2-6 Grade	2
Tamper Protection	Internal

Environmental

EN50130-5 class	Class II
IP Rating	3X
Temperature range	-15°C - +40°C

Housing

Colour	White
Material	ASA
Contact Dimensions (mm)	65 x 13 x 13
Magnet Dimensions (mm)	65 x 13 x 13

Electrical

Connection type	Wired
No. of terminals	4 Wire
Contact type	Normally Closed
Contact Material	Palladium
Wire length (mm)	100

Features

Mode of operation	DP
Operation Axes (X, Y, Z)	X, Y, Z
Pull-in gap (X, Y, Z)mm	5, 30, 30
Suitable for Double Door	Yes
Connection type	Wired
No. of terminals	4 Wire

Mechanical

Colour	White
--------	-------

