



Surface Magnetic Contact

Code: SC555/AL/4CX

SC555 | Surface Contact | Grade 2 | Aluminium | Non-resistored

This surface mounted magnet contact can be used in security systems up to and including grade 2 and environmental class II as specified in EN50131-1 and is compliant with EN50131-2-6. It operates as a normally closed circuit going open when the magnet is removed. This contact is not suitable for ferrous surfaces

Features & Benefits

- 4 Core pre-wired
- 15mm operating gap
- EN50131-2-6 Grade 2
- Environmental Class II
- Size 43 x 17 x 19mmn



Security

EN50131-2-6 Grade	2
Tamper Protection	Internal

Environmental

EN50130-5 class	Class II
IP Rating	3X
Temperature range	-10°C - +40°C

Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	35 x 15 x 10
Magnet Dimensions (mm)	35 x 15 x 10

Electrical

Connection type	Wired
No. of terminals	4 Wire
Contact type	Normally Closed
Contact Material	Rhodium
Wire length (mm)	1000

Features

Mode of operation	DP
Operation Axes (X, Y, Z)	Z, Y
Pull-in gap (X, Y, Z)mm	15, 15
Suitable for Double Door	Yes
Connection type	Wired
No. of terminals	4 Wire

Mechanical

Colour	Aluminium
--------	-----------

