

DC138S60

Inbouwcont., met flens, 6m kabel, afstand ca. 12 mm, REQ Security grade 3

Requirements for grade 3 magnetic contacts

The grade 3 magnetic contacts are high security contacts which do meet the following requirements: preciseness of opening distance, magnet polarisation, strength of the magnet

Model with built in EOL resistors available

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



Details

- EN 50131-2-6 Grade 3 and VDS certified
- 6 m cable
- Tamper protected
- Several European certifications

DC138S60

Inbouwcont., met flens, 6m kabel, afstand ca. 12 mm, REQ Security grade 3

Technical specifications

General

Application type	Recessed Mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination

Wired/wireless

Wired-wireless	Wired
----------------	-------

Electrical

Operating voltage	max. 40 V (permissible operating voltage)
Voltage	max 100V DC
Contact power	max 6W or 6 VA
Switching current	max 500mA
Contact resistance	max 0.15 Ohm

Physical

Physical dimensions	Ø 3.2 mm x 6 m (cable dimensions)
Colour	White
Material	ABS
Dimensions magnet	6 x 19 mm
Dimensions contact / sensor	8 x 32 mm with installation flange EF 8/20
Operating gap	12 mm

Environmental

Operating temperature	-25 to 70°C
IP rating	IP67 class 3

Standards & regulation

EN50131 grade	Grade 3
---------------	---------



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 14 January 2021 - 13:50