

SIGNAL CABLE - 2X2X0.5 PVC SHIELDED

CARATTERISTICHE TECNICHE

CONDUTTORI

Rigid Bare copper $\varnothing$ 0,48mm

ISOLAMENTO

PVC $\varnothing$ 1 mm

Colour code Pair 1 = Blu - Red
Pair 2= Verde-Giallo

ASSEMBLY

Conductors Twisted in Pairs

SCREEN


Alluminium Poliester Tape
Drain Wire Bare copper 0,5mm

Ssheath

PVC Grey Outher diamter 4,6mm +/- 0,2

PACKAGING AVAILABLE

Coil 100mt.
Coil 200mt.
Spool 500 mt.



MARKING

KTS s.r.l. SIGNAL CABLE TWISTED 2X2XAWG24
UNEL 36762 U/o 400 V (metrica) LOTTO n°: XX/XX
SETT/ANNO CE MADE IN ITALY

CARATTERISTICHE ELETTRICHE

TEST VOLTAGE

1000 V

INSULATION RESISTANCE

> 200 M Ω /Km

TEMPERATURE RANGE

-10°/ +70°

BENDING RADIUS

10 X $\varnothing$

STANDARDS

Insulation and sheath	CEI EN 50363
Not propagation of flame	IEC 60332-1-2
	CEI EN 50267-2-3

European directive Rohs 2011/65/EU

Euroclasse CPR

Norma Armonizzata: EN 50575:2014 + A1:2016



Reazione al fuoco :

Eca

Sostanze pericolose: Nessuna

Marcatura: **CE**

PRODOTTI:

Code	Type	$\varnothing$ +/-0,2mm	Packaging
PVRS22AWG24	SIGNAL CABLE PVC 2X2XAWG24 SHIELDED	4,6	M100 - M200 - B500