

DH-IPC-EBW8842-AS

8 MP IR Fisheye WizMind Network Camera



WizMind

Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

Series Overview

With fisheye lens, Dahua Fisheye series camera can realize 360° surveillance, and it is widely applied in various scenes such as airports, shopping centers, banks and hotels.

Functions

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Fisheye VR

With intelligent algorithm, Dahua Fisheye VR technology provides interactive 3-dimensional dynamic view through fisheye image. Dahua fisheye VR supports various interactive modes, such as original, bowl, cylinder and asteroid, providing more interactive experience.

Heat Map

Dahua heat map technology is used to display the crowd density and people appearance probability. Display the crowd status by different colors. Generally, the crowd status is the statistics of people quantity in space and time dimensions.

- 8 MP 1/1.7" CMOS image sensor, low luminance, and high definition image.
- Outputs max. 8M (3280 × 2480) @25/30 fps.
- Built-in IR LED, and the max. illumination distance is 10 m.
- Intelligent monitoring: Intrusion, tripwire, heat map, and people counting.
- SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built-in dual-array Mic and speaker.
- 12 VDC/PoE power supply.
- IP67 and IK10 protection.



People Counting

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs reports to meet your requirements.

Protection (IP67, IK10, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normal after soaking in 1 m deep water for 30 minutes.

IK10: The enclosure can stand the punch more than 5 times from a 5 kg hammer falling from a height of 40 cm (Impact energy is 20J).

Wide voltage: The camera allows ±30% (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification

Camera

Image Sensor	1/1.7" CMOS
Max. Resolution	3280 (H) × 2480 (V)
ROM	4 GB
RAM	2 GB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.01 Lux@F2.0 (Color, 30 IRE) 0.001 Lux@F2.0 (B/W, 30 IRE) 0 Lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination Distance	up to 10 m (32.81 ft) (IR)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	3 (IR LED)

Lens

Lens Type	Fixed-focal			
Lens Mount	M12			
Focal Length	1.85mm			
Max. Aperture	F2.0			
Field of View	Horizontal: 185°; Vertical: 180°			
Iris Control	Fixed			
Close Focus Distance	0.4 m (1.31 ft)			
DORI Distance	Detect	Observe	Recognize	Identify
	40.0 m (131.23 ft)	16.0 m (52.49 ft)	8.0 m (26.2 ft)	4.0 m (13.12 ft)
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.			

Smart Event

Heat Map	Yes
----------	-----

Professional, intelligent

IVS (Perimeter Protection)	Tripwire, intrusion (the two functions support accurate detection of human)
People Counting	Supports 4 rules to count the number of people entering, exiting, and staying separately. It will trigger alarm linkage when the number of people who entering, exiting or staying exceeds the threshold. It can display and export reports based on year, month, week, day or custom time. Supports 4 rules to count the number of people in area and will trigger alarm linkage when the average strand time or people number in the area exceeds the threshold. It can display and export reports based on month, week, day or custom time

Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
--------------	---

Video

Video Compression	H.265; H.264; H.264H; MJPEG (Only supported by the sub stream)
Smart Codec	Smart H.265+; Smart H.264+
Video Frame Rate	Main stream: 3280 × 2480@(1–25/30 fps) sub stream: 704 × 576@(1–25/30 fps) third stream: 1280 × 960@(1–25/30 fps) Fisheye mode: 1O (3280 × 2480) 1P (4096 × 1024) 2P (2432 × 2432) 1R (1216 × 1216) 2R (2432 × 2432) 4R (2432 × 2432) 1O + 3R (2432 × 2432) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Stream Capability	3 streams
Resolution	3280 × 2480; 2880 × 2160; (3M) 2048 × 1536; 1.3M (1280 × 960); D1 (704 × 576/704 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H264: 8 kbps–16384 kbps H265: 3 kbps–13891 kbps
Day/Night	Auto(ICR)/Color/B/W
BLC	Yes
HLC	Yes
WDR	DWDR
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Gain Control	Auto
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest (Rol)	Yes (4 areas)
Defog	Yes
Privacy Masking	4 areas

Audio

Built-in MIC	Yes, built-in dual Mic
Audio Compression	PCM; G.711A; G.711Mu; G.726; G.723

Alarm

Alarm Event	No SD card; SD card full; SD card durability warning; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; scene changing; audio detection; voltage detection; external alarm; people counting in area; stay detection; people counting; security exception
-------------	---

Network

Network Port	RJ-45 (10/100/1000 Base-T)
--------------	----------------------------

SDK and API	Yes
Security	Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec; P2P (Only supported by general version)
User/Host	20
Storage	FTP; SFTP; Micro SD card (support max. 256 G); NAS
Browser	IE: IE11, IE10 Chrome: 48.0.2564.116 Firefox: 48.0.2 Edge: 42.17134.1.0
Management Software	Smart PSS; DSS; DMSS

Certification

Certifications	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL62368-1 & CAN/CSA C22.2 No. 62368-1-14
----------------	---

Port

Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Alarm Input	2 channel in: wet contact, 5mA 3V–5 VDC
Alarm Output	2 channels out: dry contact, 1,000mA 30 VDC/500mA 50 VDC

Power

Power Supply	12 VDC/POE+ (802.3at)
Power Consumption	Basic: 6.5 W (12 VDC); 6.1 W (PoE) Max. (ICR + IR intensity): 13 W (12 VDC); 13.9 W (PoE) Heating: 3 W (12 VDC); 3 W (PoE)

Environment

Operating Temperature	–40 °C to +60 °C (–40 °F to +140 °F)
Operating Humidity	≤95%
Storage Temperature	–30 °C to +70 °C (–22 °F to +158 °F)
Protection	IP67; IK10

Structure

Casing	Metal
Product Dimensions	59.8 mm × Φ149.8 mm (2.35" × Φ5.90")
Net Weight	0.79 kg (1.74 lb)
Gross Weight	1.21 kg (2.67 lb)

Ordering Information

Type	Model	Description
8MP Camera	DH-IPC-EBW8842-AS	8 MP IR Fisheye WizMind Network Camera
	IPC-EBW8842-AS	8 MP IR Fisheye WizMind Network Camera
Accessories (Optional)	PFB300C	Ceiling-mount Bracket
	PFA100	Adapting Plate
	PFB302S	Wall-mount Bracket
	PFA132-E	Junction Box

Accessories

Optional



Junction Mount	Ceiling Mount	Wall Mount
PFA132-E	PFA100+PFB300C	PFA100+PFB302S

Dimensions (mm[inch])

